

PRODUCT
Colours



180
PYTHON

Hybrid



320
SUNLIGHT

Hybrid



510
ENLIGHTEN

Hybrid



530
WREATH

Hybrid



710
ORACLE

Hybrid



730
DOLPHIN

Hybrid



APOLLO

Apollo captures the natural beauty of timber with the best attributes of a laminate and vinyl flooring. The innovative Hybrid flooring delivers astonishing durability and impact resistance. With Trigon® core technology and a scratch resistance surface this beautiful and durable floor is able to withstand heavy foot traffic.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed.

PRODUCT

Specifications

APOLLO - Hybrid Product Details

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	5.8mm	Surface	Embossed
Wear Layer	0.3mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1220mm (L) x 180mm (W)	Substrate Layer	Trigon® Core Technology (Limestone Composite)
Planks per Box	10		
M ² per Box	2.196m ²	Backing Layer	1.5mm EVA
M ² per Pallet	131.76m ²	Profile	Micro Bevel
Colours	6	Protective Coating	UV Coating
Installation Method	Drop Lock		

Performance

Dimensional Stability	Length: 0.05% Width: -0.05% Curling: 0.00%	ISO 23999
Thermal Resistance	0.061m ² .K/w	EN 12667
Thermal Conductivity	0.101 W/(m.K)	EN 12667
Abrasion Rating	Group T	EN 660-2
Swelling After Submersion in Water	0.1%	ISO 24336
Impact Sound Reduction	Ln,W 50 IIC 60	ISO 10140-3 ASTM E492-09
Light Fastness	Grade 6	EN ISO 105-B02
Fire Classification	CRF 10.6kW/m ² Smoke Value 92% minutes	ISO 9239
Slip Resistance	P3	AS/NZ 4586 - 2013
Residential Warranty*	15 Years	
Commercial Warranty †	3 Years	

Sustainability

VOC Rating	Passes CETEC VOC test
------------	-----------------------

Test results and certificates are available on request.

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Hybrid products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Hybrid Installation Instructions.

*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Hybrid Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst hybrid products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst Floors commercial account manager.

