NAPIER

Red Earth

Colours



185 IRON BARK





TASSIE OAK



Flooring



BLACKBUTT

Hybrid Flooring



SPOTTED GUM

Hybrid Flooring



NORTHERN BOX

Hybrid Flooring



FOREST RED

Hybrid Flooring



Swatch colours are for guide purposes only.

NAPIER

Napier delivers astonishing durability and impact resistance. With innovative Trigon® Core Technology, this waterproof[^] product remains stable in extreme temperatures and is ready to withstand an army of foot traffic.

Red Earth

Specifications

NAPIER-Hybrid Product Details

Technical Data				
Туре	Hybrid	Finish	Matte	
Plank Thickness	5.5mm	Surface	Embossed	
Wear Layer	0.55mm	Profile	Micro Bevel	
Dimensions	1813mm (L) x 144mm (W)	Top Layer	Decorative Film & Wear Layer	
Planks per Box	9	Culpatrata Lavar	Trigon® Core Technology (Limestone Composite)	
M² per Box	2.35m ²	Substrate Layer		
M² per Pallet	112.80m²	Backing Layer	1.5mm EVA	
Colours	6	Protective Coating	UV Coating	
Installation Method	Drop Lock			

Type	Hybrid	Finish	Matte
Plank Thickness	5.5mm	Surface	Embossed
Wear Layer	0.55mm	Profile	Micro Bevel
Dimensions	1813mm (L) x 144mm (W)	Top Layer	Decorative Film & Wear Laye
Planks per Box	9	Substrate Layer	Trigon® Core Technology (Limestone Composite)
M² per Box	2.35m ²		
M ² per Pallet	112.80m²	Backing Layer	1.5mm EVA
Colours	6	Protective Coating	UV Coating
Installation Method	Drop Lock		

Performance		
Classification	23, 34	ISO 10874
Dimensional Stability	≤ 0.03%	ISO 23999
Thermal Resistance	0.05 m² K/W	EN 12667
Thermal Conductivity	0.1 W/(m.K)	EN 12667
Abrasion Rating	Group T	EN 660-2
Residual Indentation	≤ 0.03mm	EN 433 / ISO 24343-1
Swelling After Submersion in Water	0%	ISO 24336
Castor Chair	No Damage	EN 425
Impact Sound Reduction	Available on Request	ISO 10140-3 ASTM E492-09
Light Fastness	≥6	ISO 105-BO2
Chemical Resistance	Class 0, Excellent	EN 425
Flammability Rating	CRF 10.5/m ² Smoke Value 170% minutes	AS ISO 9239
Slip Resistance	R10	AS / NZ 4586-2013
Residential Warranty*	Lifetime	
Commercial Warranty [†]	15 Years	

Sustainability	
VOC Rating	DIBT Certified, REACH Compliant & CETEC

Test results and certificates are available on request.

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Hybrid products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Hybrid Installation Instructions.

Subject to proper installation and maintenance.













^{*}These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Hybrid Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst hybrid products) available from

your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.
†Terms and conditions apply to all commercial warranties — contact your Godfrey Hirst Floors commercial account manager.