

PRODUCT
Colours



170
STELLA

Luxury
Vinyl Plank



180
SPLENDOUR

Luxury
Vinyl Plank



300
SOLAR

Luxury
Vinyl Plank



350
STARLIGHT

Luxury
Vinyl Plank



500
RADIANCE

Luxury
Vinyl Plank



520
GLIMMER

Luxury
Vinyl Plank



540
COSMIC

Luxury
Vinyl Plank



545
COASTAL
BLACKBUTT

Luxury
Vinyl Plank



555
QLD SPOTTED
GUM

Luxury
Vinyl Plank



560
ASTRO

Luxury
Vinyl Plank



720
GALAXY

Luxury
Vinyl Plank



750
MOONSTONE

Luxury
Vinyl Plank



POLARIS ^{DS} LUXURY VINYL PLANK

With an exceptionally realistic timber look, the Polaris ^{DS} range of luxury vinyl plank provides a flexible, durable and water resistant floor suitable for all residential interiors. Performance Classification 23-32.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed.

PRODUCT

Specifications

POLARIS Direct Stick - Vinyl Plank Product Details

Technical Data		Technical Data	
Type	Luxury Vinyl Plank	Colours	12
Plank Thickness	3mm	Protective Coating	PU Coating
Wear Layer	0.3mm	Finish	Matte
Dimensions	1219mm (L) x 228mm (W)	Surface	Woodgrain - Semi Wild
Planks per Box	13	Profile	Square Edge
M ² per Box	3.62m ²	M ² per Pallet	202.72m ²

Installation Method Direct Stick  Please refer Installation instructions for further details

Performance

Classification	23, 32	ISO 10582
Dimensional Stability	≤ 0.25%	EN 434
Abrasion Rating	Group P	EN 660-1
Residual Indentation	< 0.1mm	EN 433
Furniture Leg	No Damage	EN 424
Castor Chair	No Damage	EN 425
Curl Resistance to Heat	≤ 2mm	EN 434
Thermal Performance	0.07m ² K/W Suitable - max. 27°C	EN 12667
Light Fastness	≤ 6	EN ISO 105-BO2
Chemical Resistance	Good Resistance	EN 423
Electrical Propensity	Pass	EN 1815
Slip Resistance	R10	AS/NZ 4586-2013
Residential Warranty*	10 Years	
Commercial Warranty†	3 Years	
Reaction to Fire	CRF10.4kW/m ² Smoke Value 104% Minutes	
Suitable for wet areas	Yes - subject to proper installation and maintenance	
Recommended Adhesive	Polymer 265 Adhesive - General application Roberts GS200 - Universal Vinyl Adhesive, Solvent Free, Low VOC, Green Star Compliant Holdfast 416 - Multi Purpose Sheet and Tile Adhesive	

Sustainability

VOC Rating	Available on Request
------------	----------------------

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Luxury Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst luxury vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst Floors commercial account manager.

Test results and certificates are available on request.

