



PRODUCT  
**Colours**



350  
STARLIGHT

Luxury  
Vinyl Plank



500  
RADIANCE

Luxury  
Vinyl Plank



510  
SHINE

Luxury  
Vinyl Plank



520  
GLIMMER

Luxury  
Vinyl Plank



540  
COSMIC

Luxury  
Vinyl Plank



545  
COASTAL  
BLACKBUTT

Luxury  
Vinyl Plank



555  
QLD SPOTTED  
GUM

Luxury  
Vinyl Plank



560  
ASTRO

Luxury  
Vinyl Plank



750  
MOONSTONE

Luxury  
Vinyl Plank



770  
METEOR

Luxury  
Vinyl Plank



POLARIS **EL** LUXURY VINYL PLANK


With an exceptionally realistic timber look, the Polaris **EL** range of luxury vinyl plank provides a flexible, durable and water resistant floor suitable for all residential interiors. Performance Classification 23-32.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed.

## PRODUCT

## Specifications

## POLARIS Express Lay® - Vinyl Plank Product Details

Technical Data		Technical Data	
Type	Luxury Vinyl Plank	Colours	10
Plank Thickness	5mm	Protective Coating	PU Coating
Wear Layer	0.3mm	Finish	Matte
Dimensions	1219mm (L) x 228mm (W)	Surface	Woodgrain - Semi Wild
Planks per Box	8	Profile	Square Edge
M <sup>2</sup> per Box	2.23m <sup>2</sup>	M <sup>2</sup> per Pallet	124.88m <sup>2</sup>
Installation Method	Express Lay®  Please refer Installation instructions for further details		



## Performance

Classification	Residential 23, Commercial 32	ISO 10582
Dimensional Stability	≤ 0.25%	EN 434
Abrasion Rating	Group P	EN 660-1
Residual Indentation	< 0.1mm	EN 433
Furniture Leg	No Damage	EN 424
Castor Chair	No Damage	EN 425
Curl Resistance to Heat	≤ 2mm	EN 434
Thermal Performance	0.07m <sup>2</sup> K/W Suitable - max. 27°C	EN 12667
Impact Sound Reduction	Ln,W 60 IIC 50	ISO 10140-3 ASTM E492-09
Light Fastness	≤ 6	EN ISO 105-BO2
Chemical Resistance	Good Resistance	EN 423
Electrical Propensity	Pass	EN 1815
Slip Resistance	P1, R10	AS/NZ 4586-2013
Commercial Warranty†	3 Years	
Residential Warranty	10 Years	
Reaction to Fire	CRF 10.4kW/m <sup>2</sup> Smoke Value 83% Minutes	AS/ISO 9239
Suitable for wet areas	Yes - subject to proper installation and maintenance	
Recommended Adhesive	Roberts 656 - Pressure Sensitive, Solvent Free, Low VOC, Green Star Compliant RLA GS300 - Pressure Sensitive, Solvent Free, Low VOC, Green Star Compliant Holdfast 777 - Pressure Sensitive, Solvent Free, VOC Compliant	

## Sustainability

VOC Rating	Passes CETEC VOC Test
------------	-----------------------

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

\*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Luxury Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst luxury vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com).

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst Floors commercial account manager.

Test results and certificates are available on request.