

PRODUCT
Colours



1001
GREY MIST

Vinyl Plank



1301
WHISPER

Vinyl Plank



3001
DUNE

Vinyl Plank



5001
BISCOTTI

Vinyl Plank



5101
CANOE

Vinyl Plank



5201
HUSK

Vinyl Plank



5301
TRUFFLE

Vinyl Plank



5401
MOCHA

Vinyl Plank



5501
CHOCOLATE

Vinyl Plank



7001
SILVER BELL

Vinyl Plank



7401
CASTLE

Vinyl Plank



7501
STONEWALL

Vinyl Plank



VEGA VINYL PLANK

With an exceptionally realistic timber look, the Vega range of luxury vinyl plank provides a flexible, durable and water resistant floor suitable for many commercial interiors. Performance Classification 23/33/42.

The Vega **DS** direct stick option is great for installations in wet areas as it can be glued directly to a variety of subfloors, including concrete.


For another installation option, see Vega **EL**.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed.

PRODUCT

Specifications

VEGA - Vinyl Plank Product Details

| Technical Data | | Technical Data | |
|------------------------|---|---------------------------|-----------------------|
| Type | Vinyl Plank | Colours | 12 |
| Plank Thickness | 2.5mm | Protective Coating | UV Coating |
| Wear Layer | 0.55mm | Finish | Matte |
| Dimensions | 1227mm (L) x 187mm (W) | Surface | Embossed in Register |
| Planks per Box | 16 | Profile | Micro Bevel |
| M ² per Box | 3.671m ² | M ² per Pallet | 275.325m ² |
| Installation Method | Direct Stick  Please refer Installation instructions for further details | | |



Performance

| | | |
|------------------------|---|------------------------------|
| Classification | Heterogeneous Vinyl Flooring Residential 23, Commercial 33, Industrial 42 | EN 649 ISO 10874 (EN 685) |
| Dimensional Stability | ≤ 0.10% | EN 434 |
| Abrasion Rating | Group T | EN 660-2 |
| Residual Indentation | < 0.05mm | EN 433 |
| Furniture Leg | No Damage | EN 424 |
| Castor Chair | No Damage | EN 425 |
| Thermal Performance | 0.07m ² K/W | EN 12667 |
| Impact Sound Reduction | Ln,w 57 | ISO 10140-3 |
| Light Fastness | ≥ 6 | EN ISO 105-B02 |
| Chemical Resistance | Good Resistance | EN 423 |
| Electrical Propensity | Pass | EN 1815 |
| Reaction to Fire | CRF 10.9kW/m ² Smoke Value 59% Minutes | AS ISO 9239 |
| Slip Resistance | R10 / P3 | AS 4586-2013 |
| Residential Warranty* | 25 Years | |
| Commercial Warranty† | 10 Years | |
| Recommended Adhesive | Refer to Godfrey Hirst Adhesive Guide. www.godfreyhirst.com | |

Sustainability

| | |
|---------------|---|
| VOC Rating | Floorscore, CETEC & E1 compliant for VOC emission rate limits |
| Accreditation | Manufactured under a management system certified as complying with ISO9001 & ISO14001 |

Test results and certificates available on request.

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst Floors commercial account manager.