Express Lay®



Colours



GREY MIST



1303 WHISPER



3003 DUNE



5003 BISCOTTI



5103 CANOE



5203 HUSK

Vinyl Plank



Vinyl Plank



Vinyl Plank

Vinyl Plank



5303 TRUFFI F



5403 MOCHA



5503 CHOCOLATE



7003 SILVER BELL



7403 CASTLE



7503 STONEWALL

Vinyl Plank

Vinyl Plank

Vinyl Plank

Vinyl Plank

Vinyl Plank

Vinyl Plank



VEGA VINYL PLANK

With an exceptionally realistic timber look, the Vega range of luxury vinyl plank provides a flexible, durable and water resistant floor suitable for many commercial interiors.

With its Express Lay® feature, Vega 🕕 has been designed for a quick and easy installation by simply using a pressure sensitive adhesive to ensure added stability and performance (please refer to installation guidelines). Classification 23/33/42.

For another installation option, see Vega 🗓 .



Product images on this flyer should only be used as a guide or point or reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed.

Express Lay®



PRODUCT

Specifications

VEGA - Vinyl Plank Product Details

Technical Data		Technical Data	
Туре	Vinyl Plank	Colours	12
Plank Thickness	5.0mm	Protective Coating	UV Coating
Wear Layer	0.55mm	Finish	Matte
Dimensions	1227mm (L) x 187mm (W)	Surface	Embossed in Register
Planks per Box	8	Profile	Micro Bevel
M ² per Box	1.836m²	M ² per Pallet	128.52m²

Installation Method Express Lay®
Please refer Installation instructions for further details

Performance		
Classification	Heterogeneous Vinyl Flooring Residential 23, Commercial 33, Industrial 42	EN 649 ISO 10874 (EN 685)
Dimensional Stability	≤ 0.10%	EN 434
Abrasion Rating	Group T	EN 660-2
Residual Indentation	≤ 0.05mm	EN 433
Furniture Leg	No Damage	EN 424
Castor Chair	No Damage	EN 425
Thermal Performance	0.07m² K/W	EN 12667
Impact Sound Reduction	Ln,w 60 IIC 50	ISO 10140-3 ASTM E492-09
Light Fastness	≥ 6	EN ISO 105-B02
Chemical Resistance	Good Resistance	EN 423
Electrical Propensity	Pass	EN 1815
Reaction to Fire	CRF 9.7kW/m² Smoke Value 103% Minutes	AS ISO 9239
Slip Resistance	R10 / P3	AS 4586-2013
Residential Warranty*	25 Years	
Commercial Warranty [†]	10 Years	
Recommended Adhesive	Refer to Godfrey Hirst Adhesive Guide. www.godfreyhirst.com	
Sustainability		
VOC Dating	Flooreners OFTEO 9 E1 compliant for VOC om	tantan nata Basta

VOC Rating	Floorscore, CETEC & E1 compliant for VOC emission rate limits	
Accreditation	Manufactured under a management system certified as complying with ISO9001 & ISO14001 by an accredited certification body	

Test results and certificates available on request.

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.

†Terms and conditions apply to all commercial warranties — contact your Godfrey Hirst Floors commercial account manager.













