




Stonehaven



300
**Natural
Oak**



540
**Weathered
Gum**



550
Blackbutt



710
**Silk
Oak**



750
**Ash
Oak**



180
**Toasted
Oak**



505
**Lime Washed
Blackbutt**



520
**Copper
Oak**



While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice.
*Subject to proper installation, maintenance and local building code/regulatory approval.

Stonehaven

Stonehaven is a stunning hybrid floor that is extremely hard wearing, stable and has a waterproof surface[^], making it perfect for use in all areas of your home. With micro bevel edges and an embossed matte finish, Stonehaven authentically replicates a natural timber wood grain look. A scratch and stain resistant surface coating means Stonehaven can easily withstand the everyday wear and tear of busy family homes.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	6.5mm	Surface	Embossed
Wear Layer	0.5mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1500mm (L) x 228mm (W)	Substrate Layer	Trigon [®] Core Technology (Limestone Composite)
Planks per Box	6	Backing Layer	1.5mm EVA
M² per Box	2.052m ²	Profile	Micro Bevel
M² per Pallet	102.6m ²	Protective Coating	PUR & Scratch Resistance
Colours	8		
Installation Method	Unipush [®] (Tap Fold-Down)		

Performance

Dimensional Stability	Length 0.05% Width 0.00% Curling 0.0%	ISO23999
Abrasion Rating	Group T	EN 660-2
Impact Sound Reduction	Test Application	Ln'T,w Result
	150mm Slab + 28mm Furrings + 10mm Plasterboard	50
	200m Slab	54
	200mm Slab + 28mm Furrings + 10mm Plasterboard	49
	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	46
	250mm Slab + 28mm Furrings + 10mm Plasterboard	48
Light Fastness	Grade 6	EN ISO 105-B02
Fire Classification	10.9kW/m ² Smoke Value 81% minutes	ISO 9239
Slip Resistance	P3	AS/NZ 4586 - 2013
Residential Warranty*	25 Year Hybrid Limited Residential Warranty	
Commercial Warranty†	Commercial Warranty available on request	

Sustainability

Indoor Air Quality	Green Building Council compliant for VOC emission rate limits
Global GreenTag	GreenRate Level A certified



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of the Godfrey Hirst continuous improvement program, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. All Godfrey Hirst Hybrid Floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Floors Installation Instructions. *This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com. †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.