

## PRODUCT SPECIFICATIONS:

<b>PILE CONTENT:</b>	50% Wool, 50% Synthetic Featuring <b>TEXTURE LOC®</b>
<b>PILE WEIGHT:</b>	881 gm/m <sup>2</sup> - 26 oz/yd <sup>2</sup>
<b>PILE HEIGHT:</b>	6 mm
<b>CARPET THICKNESS:</b>	8 mm
<b>MACHINE GAUGE:</b>	2.54 mm - 1/10"
<b>STITCH RATE:</b>	As required to provide a carpet of total pile mass, pile height and machine gauge as specified.
<b>WIDTH:</b>	3.66 metres
<b>PRIMARY BACK:</b>	Heat Stabilised Woven Polypropylene
<b>SECONDARY BACK:</b>	Woven Jute
<b>FIRE RATING:</b>	AS/ISO 9239.1:2003
<b>GRADING:</b>	Residential Heavy Duty & Stairs
<b>ENVIRONMENTAL ACCREDITATION:</b>	Achieves Certification under the ACCS Environmental Classification Scheme.
<b>VOC EMISSIONS:</b>	Meets ACCS Environmental Classification Criteria
<b>COMMERCIAL WARRANTY:</b>	7 Year Limited Manufacturers Defect Warranty
<b>TOLERANCE:</b>	Manufactured to A.S. 1385 tolerances.
<b>INSTALLATION:</b>	To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining).
<b>COLOUR VARIATION:</b>	Colour variation may occur between sample and production due to dye lot tolerances.
<b>MATERIAL VARIATION:</b>	Product specifications may change without notice due to raw material availability.
<b>SHADING:</b> (Permanent Pile Reversal)	Cut pile carpets have a propensity to shade. This is not a manufacturing fault further information can be obtained from the Carpet Institute of Australia leaflet.
<b>COUNTRY OF MANUFACTURE:</b>	Australia