

PRODUCT SPECIFICATIONS:

| | |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------|
| PILE CONTENT: | 100% Wool |
| PILE WEIGHT: | 1356 gm/m ² – 40 oz/yd ² |
| PILE HEIGHT: | High 8mm – Low 4mm |
| CARPET THICKNESS: | 11mm |
| MACHINE GAUGE: | 4mm - 5/32" |
| STITCH RATE: | As required to provide a carpet of total pile mass, pile height and machine gauge as specified. |
| WIDTH: | 3.66 metres |
| PRIMARY BACK: | Heat Stabilised Woven Polypropylene |
| SECONDARY BACK: | Woven Jute |
| FIRE RATING: | AS/ISO 9239.1:2003 (Available on request.) |
| GRADING: | Residential Extra Heavy Duty & Stairs Contract Medium Duty & Stairs |
| ENVIRONMENTAL ACCREDITATION: | Achieves Level 3 Certification under the ACCS Environmental Classification Scheme |
| VOC EMISSIONS: | Meets ACCS Environmental Classification Criteria |
| WARRANTIES: | 15 Year Limited Residential Wear Warranty |
| TOLERANCE: | Manufactured to A.S. 1385 tolerances. |
| INSTALLATION: | To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining). |
| COUNTRY OF MANUFACTURE: | Australia |