

## PRODUCT SPECIFICATIONS:

|  |  |
|--|--|
| <b>PILE CONTENT:</b>                         | 100% wool  |
| <b>PILE WEIGHT:</b>                          | 2034 gm/m <sup>2</sup> – 60 oz/yd <sup>2</sup>   |
| <b>PILE HEIGHT:</b>                          | 11.5 mm  |
| <b>CARPET THICKNESS:</b>                     | 12.5 mm  |
| <b>MACHINE GAUGE:</b>                        | 3.175mm - 1/8"   |
| <b>STITCH RATE:</b>                          | As required to provide a carpet of total pile mass, pile height and machine gauge as specified.  |
| <b>WIDTH:</b>                                | 3.66 metres  |
| <b>PRIMARY BACK:</b>                         | Heat Stabilised Woven Polypropylene  |
| <b>SECONDARY BACK:</b>                       | Woven Jute   |
| <b>GRADING:</b>                              | Residential Extra Heavy Duty & Stairs<br>Contract Heavy Duty & Stairs  |
| <b>ENVIRONMENTAL ACCREDITATION:</b>          | Certified under the ACCS Environmental Classification Scheme   |
| <b>VOC EMISSIONS:</b>                        | Exceeds ACCS Green Label criteria  |
| <b>WARRANTIES:</b>                           | 15 Year Limited Residential Wear Warranty  |
| <b>TOLERANCE:</b>                            | Manufactured to A.S. 1385 tolerances.  |
| <b>INSTALLATION:</b>                         | To be laid in accordance with AS/NZS 2455.1:2007<br>Seam sealer must be applied to all seams (prior to joining).   |
| <b>SHADING:</b><br>(Permanent Pile Reversal) | Cut pile carpets have a propensity to shade. This is not a manufacturing fault further information can be obtained from the Carpet Institute of Australia leaflet. |
| <b>COUNTRY OF MANUFACTURE:</b>               | Australia  |