Metroscape



TECHNICAL SPECIFICATIONS

| Collection: | Education |
|-----------------------------|--|
| Country of Origin: | Australia |
| Colours: | 8 Standard |
| Yarn: | 100% Statron Plus® Solution Dyed Nylon |
| Surface Texture: | Textured Loop Pile |
| Gauge: | 47.2/10cm (1/12th Gauge) |
| Total Product Thickness: | 6 (+/- 1.0)mm |
| Pile Height: | 3.5 (+/- 1.0)mm |

| Pile Weight: | 610g/m² (18oz) |
|--------------------------------|-------------------------|
| Backing: | Enviro Bac® |
| Carpet Tiles & Planks Size: | 500mm x 500mm |
| Installation Method: | Direct Stick |
| Туре: | Carpet Tiles and Planks |
| Units Per Box: | 20.00 |
| m² per box: | 5 |

PERFORMANCE

Anti-Static: (AATCC 134) <3.5KV at 21°C & 20% Relative Humidity

Flammability: CRF 4.0kW/m² (Direct Stick)~ Colourfast to light: (ISO 105-B-02-1994) 6-7 Light Reflectance: Available on Request Stain Resistance: Stain Warden®

Biocontaminant Control: Bioshield® Antimicrobial Control ACCS Rating: Contract Extra Heavy Duty - 4 Star Contract Guarantee: 15 Years Available on Request* Smoke Value: 274% minutes (Direct Stick)

SUSTAINABILITY

PVC Minimisation: **PVC Free**

Green Building Council compliant for VOC emission rate limits Indoor Air Quality:

Product Transparency: Declare Red List Free

Green Star: Environmental Certification Scheme (ECS). Level 4 Maximum Points - Certificate #20047 Accreditation: Manufactured under a quality, environmental and health and safety system certified and complying with ISO 9001, ISO 14001 and ISO 45001 by accredited certification bodies.















Metroscape









680 MARMALADE



740 IRON



METEOR



NIGHT SPELL



790 OBSIDIAN



OXFORD SKY



970 BASIL

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.

Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling. ~Test results and certificates are available on request.

*Guarantee is in addition to any rights consumers may have under Australian consumer laws.

Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.